

140 Darling Road, East Malvern, Vic. 3145, Australia
 PO Box 1215
 Darling, Vic. 3145
 Telephone: (03) 9571 7719 International: 61 3 9571 7719
 Fax: (03) 9571 9977 International: 61 3 9571 9977
 E-mail: sales@interscientific.com.au
 Web: www.interscientific.com.au

Metra Radebeul




ITEM	PART No	DESCRIPTION	QTY	UNIT \$	EXT. \$
1	KS80D	KS80D Piezoelectric Vibration Accelerometer - Top exit connector	1	445.00	445.00

Features

ICP compatible voltage output guarantees low EMI under rough environmental conditions
 Dust and water protected (IP67 protection grade)
 Insulated mounting base to avoid ground loop problems
 Double shielding for best EMI protection
 M12 connector for easy assembly
 Rugged double sealed stainless steel case

Specifications

Output: ICP compatible
 Voltage Sensitivity: 100 mV/g ($\pm 5\%$ tolerance)
 Transverse Sensitivity: $< 3\%$
 Measuring Range: ± 55 g
 Linear Frequency Range: 0.3 - 14000 Hz (± 3 dB)
 Resonant Frequency: > 23 kHz ($+25$ dB)
 Constant Current Supply: 2 - 20 mA
 Output Impedance: $< 250 \Omega$
 Operating Temperature Range: -20 to 90°C
 Weight: 70 g
 Dimensions: 34 (H) x 22 mm (W)
 Cable Connection: Axial
 Socket: Binder 713
 Mounting Thread: M8



2	086G/W	Shielded cable, 5 m long, PUR jacket \varnothing 6 mm, with angled (W) or straight (G) plug Binder 713 (IP67) and BNC plug	1	85.00	85.00
3	085G/W	Shielded cable, 5 m long, PUR jacket \varnothing 6 mm, with angled (W) or straight (G) plug Binder 713 (IP67) and pigtail ends	1	85.00	85.00

Terms & Conditions

DISCOUNT:	25-50 Units: Less 5%
	50+ Units: Call to discuss
DELIVERY:	\$10.00 Airbag
AVAILABILITY:	Ex Stock
GST APPLICABLE:	+10% GST has not yet been applied
WARRANTY:	12 months as per manufacturers standard
PAYMENT:	Visa/Mastercard
VALIDITY:	30 - days

(I.S.I. is the trade name of Ninth Septelux Pty Ltd A.C.N. 005 756 114 A.B.N. 79 482 457 715)