



MONARCH INSTRUMENT

Innovation in Instrumentation

<u>ITEM</u>	<u>PART No</u>	<u>DESCRIPTION</u>	<u>QTY</u>	<u>UNIT \$</u>	<u>EXT. \$</u>
1	6180-022	SLS-230 Smart Laser Sensor with 230 VAC PR Universal recharger, SLS-CA-BNC output cable, 12 inches of T-5 reflective tape, and N.I.S.T. traceable certificate of calibration	1	1,995.00	1,995.00

Features

- "Smart" auto gain provides best performance in picking up target reflections
- "On Target" Indicator
- TTL pulse output signal inverter Switch
- Manual sensitivity knob provides dynamic fine tuning of sensor response
- On/Off or Recharge Switch
- Power/Battery Condition Indicator
- Class 3R visible Laser and Nosepiece
- Signal/Pulse/RS232 Output DIN connector Port
- External DC power or recharger Port
- Tripod Mounting Bushing (1/4 - 20 UNC)
- Will interface with Monarch Tachometers/Strobescopes and OEM Data Collectors



Specifications

- Optical: Class 3R visible laser 650nm @ 3 mW peak power
- Operating Range: up to 65 feet (19.8 m)
- Speed Range: 1-500,000 RPM
- Output Signal: TTL 5-0 VDC (user selectable polarity), RS232 (ASCII)
- Operating Temp: (0° to 40°C)
- Dimensions: 13.74 (L) x 5.96 (W) x 5.43 cm (H)
- Mounting: 1/4 - 20" UNC bushing for tripod

Terms & Conditions

- DISCOUNT: 0-10 Units: Nett
- DELIVERY: \$10.00 Airbag
- AVAILABILITY: Usually Ex Stock
- GST APPLICABLE: +10% GST has not yet been applied
- WARRANTY: 12 months as per manufacturers standard
- PAYMENT: Visa/Mastercard
- VALIDITY: 30 - days