

140 Darling Road, East Malvern, Vic. 3145, Australia

PO Box 1215

Darling, Vic. 3145, Australia

Telephone: (03) 9571 7719 International: 61 3 9571 7719

Fax: (03) 9571 9977 International: 61 3 9571 9977

E-mail: sales@interscientific.com.au

Web: www.interscientific.com.au



Model 6420V



Loop Powered 4-20 mA Velocity Output Sensor

<u>ITEM</u>	<u>PART No</u>	<u>DESCRIPTION</u>	<u>QTY</u>	<u>UNIT \$</u>	<u>EXT. \$</u>
1	9357255-10	0 - 1.0 IPS (0 - 12.7 mm/sec) RMS	1	495.00	495.00
2	9357255-20	0 - 2.0 IPS (0 - 50.8 mm/sec) RMS	1	495.00	495.00
<u>Features</u> Splashproof construction Top 2-Pin MIL style connector 1/4-28 mounting stud Current Output 4 - 20 mA \pm 5% 2 Ranges - 1.0 or 2.0 in/sec full scale					
<u>Specifications</u> Frequency Range:- 10 Hz - 1000 Hz (\pm 10%) 6 Hz - 2500 Hz (\pm 3dB) Temperature Range: -40 to 85°C Dimensions: 1.78" h x 0.875" across flats Weight: 75 grams Sensors include: Calibrated Current Output @ 61.5 Hz, 1/4-28 Mounting Stud, 1-Year Warranty					
2	9356686-6	Cable, 2-Pin Right Angle or Top Entry MIL/BNC 6ft molded splashproof	1	55.00	55.00
3	9356686-15	Cable, 2-Pin Right Angle or Top Entry MIL/BNC 15ft molded splashproof	1	75.00	75.00
4	9356687-15	Cable, 2-Pin Right Angle or Top Entry 15ft Braided with PVC shield	1	75.00	75.00

Terms & Conditions

DISCOUNT:	25-50 Units: Less 5%
	50+ Units: Call to discuss
DELIVERY:	\$10.00 Airbag
AVAILABILITY:	Ex Stock
GST APPLICABLE:	+10% GST has not yet been applied
WARRANTY:	12 months as per manufacturers standard
PAYMENT:	Visa/Mastercard
VALIDITY:	30 - days